



JDYX2.E245449 Fuses, Supplemental - Component

Page Bottom

Fuses, Supplemental - Component

[See General Information for Fuses, Supplemental - Component](#)

SART ENTERPRISE (HK) LTD

E245449

SUITE 613
INDUSTRIAL TRADE BLDG
57 SHANXI RD
NANJING, JIANGSU CHINA

Conditions of Acceptability:

1. These devices are intended to carry 100 percent of rated current for 4 h minimum.
2. The devices should be used only on circuits where the voltage and the short circuit available current is within the fuses interrupting ability.

Cat. No.	Size	Amps	V ac	Interrupting Rating (kA)
S0603-NN#	1.6 x 0.8 x 0.5 mm	1/2 - 5	32 V dc	0.035
S0805-NN#	2.0 x 1.25 x 0.6 mm	1/2 - 2	32 V dc	0.050
S1206-NN#	3.2 x 1.6 x 0.6 mm	1/2 - 5	32 V dc	0.050

NN indicates ampere rating of fuse.

Marking: Company name or catalog designation.

Last Updated on 2005-04-18

[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

[Copyright © 2007 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2007 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

